



Suitable for a wide range of different size batteries



Adjusts the charging profile to suit calcium batteries



Revitalises tired batteries, increasing battery life and performance\*



Optional mounting wings for permanent installation



0.6m harness allows permanent connection and features polarity protection

## **SPECIFICATIONS**

PRODUCT DETAILS		L.E.D CHARGE INDICATION			
PART NO.	PC400	BLUE LIGHT ON	Bulk charging		
TYPE INPUT	6 stage 240VAC, 50Hz, 132W	• GREEN LIGHT ON	Fully charged and maintaining, no need to turn off		
ОИТРИТ	12V	• AMBER LIGHT ON	Rejuvenation process occurring		
OUTPUT CURRENT	1, 2, 4A	• RED LIGHT ON	Indicates faulty battery		
MINIMUM START VOLTAGE	3.0V	BATTERY CHARGE TIMES			
BACK DRAIN	1mA	PC400	VOLTAGE	BATTERY SIZE	CHARGE TIME
APPROVALS	Electrical Safety, EMC	AUTOMOTIVE	12V	40-480CCA	7–24 hrs
		MARINE	12V	55-650MCA	7–24 hrs
		DEEP CYCLE	12V	7–80Ah	7-24 hrs

## **APPLICATIONS**



REPLACEMENT PARTS BCWH Fused vehicle harness BCCL Battery clips

\* Subject to battery condition